



**GREENchoice**  
ADHESIVES

# Professional Drywall Adhesive

## Physical Properties

**Type:** Polymer emulsion  
**State:** Medium-viscosity mastic  
**Color:** Beige  
**Solids:** 70%  
**Viscosity:** 200,000 cps  
**pH:** 5.0

**Calculated VOC (less water):** 4.8 g/L  
**Weight/gallon:** 11.9 lbs.  
**Flashpoint:** >200°F.  
**Freeze/thaw stability:** Stable  
**Storage life:** More than 2 years in unopened container

## Application Guidelines

**Application temperature:** Over 40°F. for adhesive and substrates

**Service temperatures:** 0°F. to 120°F.

**Method of application:** Cartridge/caulking gun

**Coverage (maximum):** Approximate length of bead according to bead diameter:

Container	1/8" bead	1/4" bead	3/8" bead
29 oz. Cartridge	355 ft	89 ft	39 ft

**Working time:** Approximately 20 minutes for a 1/4" bead

**Working surfaces:** Surfaces to be bonded should be clean, dry and free from excessive oil, grease, water, dirt or any other material that may deter adhesion.

**Cleanup:** Clean with water while adhesive is wet. Scrape off dried excess with a putty knife. Remove residue with mineral spirits or equivalent solvent. Follow solvent vendor's precautions when using solvents. NOTE: Test solvent on an out-of-the-way area to make sure it will not mar or attack the surface.

## Product Features

**Exceeds the performance requirements of the ASTM C557 and CAN/CGSB-71.25-M Specifications. Tested in accordance with E72 for racking and shearing.**

- Environmentally safe – VOC-compliant
- Bonds to plaster, wallboard, plywood, paneling, tileboard and wood
- Excellent strength
- "No sag" installation
- Reduces nail pops
- Cleans easily with water in wet state
- Post-consumer recycled cartridge and carton

## Limitations

GREENchoice Drywall is not intended for exterior applications. Not for use with metal studs. For light applications on most metals, we recommend GREENchoice Heavy Duty Construction Adhesive. For all ceiling applications, fasteners are required in addition to the adhesive. For best results, store GREENchoice Drywall above 40°F. For questions, please call our toll free Help Line 1-888-533-9043 or visit us at TitebondGreenChoice.com.

## Caution Statement

**CAUTION: EYE AND SKIN IRRITANT.** Contains ethylene glycol. Do not swallow. Do not allow eye contact or prolonged skin contact. **First Aid:** If swallowed, do not induce vomiting; contact physician. If eye contact occurs, flush eyes with water for 15 minutes. Wash skin contact areas with soap and water. If irritation from eye or skin contact areas persists, contact physician. For additional information, refer to Material Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

## Ordering Information

Cat. No.	Size	Units per Package	Weight	Packages per Pallet
7272	29 oz. Cartridge	12	37	38

Important Notice: Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.

1.888.533.9043 Help Line TitebondGreenChoice.com  
1.800.669.4583 Customer Service www.titebond.com

©2008 Franklin International. All rights reserved.

**Franklin International**

2020 Bruck Street Columbus, Ohio 43207