



GREENchoice
ADHESIVES

Weatherproof Subfloor Adhesive

Physical Properties

Type: Blend of polymer emulsions
State: Medium-viscosity mastic
Color: Off-white
Solids: 69%
Viscosity: 65,000 - 100,000 cps
pH: 6.5 - 7.5

Calculated VOC (less water): 27 g/L
Weight/gallon: 10.13 lbs.
Flashpoint: >200°F.
Freeze/thaw stability: Stable
Storage life: More than 2 years in unopened container

Application Guidelines

Application temperature: 40°F. to 100°F.

Service temperatures: 10°F. to 120°F.

Method of application: Cartridge/caulking gun

Coverage (maximum): Approximate length of bead according to bead diameter:

Container	1/8" bead	1/4" bead	3/8" bead
29 oz. Cartridge	355 ft	89 ft	39 ft

Working time: Approximately 20 minutes for a 1/4" bead

Working surfaces: Surfaces must be clean and free of any material that may deter adhesion. Apply adhesive to only one of the surfaces to be bonded. NOTE: For subfloors, nail or screw each sheet as recommended by the American Plywood Association.

Cleanup: Clean with water while adhesive is wet. Scrape off dried excess with a putty knife. Remove residue with mineral spirits or equivalent solvent. Follow solvent vendor's precautions when using solvents. NOTE: Test solvent on an out-of-the-way area to make sure it will not mar or attack the surface.

Product Features

Exceeds the requirements of the APA's AFG-01 specification and ASTM C557.

- Environmentally safe – VOC-compliant
- Fills gaps and irregularities
- Reduces the amount of nailing
- Highly water-resistant when dry
- Excellent aging qualities
- Ideal for use on wet, frozen, treated and engineered lumber
- Offers freeze/thaw stability
- Cleans easily with water in wet state
- Post-consumer recycled cartridge and carton

Limitations

GREENchoice Subfloor Adhesive is not designed for continuous submersion. For rigid plastics, metal or steel applications, we recommend GREENchoice Premium Polyurethane. For best results, store adhesive above 40°F. For questions, please call our toll free Help Line 1-888-533-9043 or visit us at TitebondGreenChoice.com.

Caution Statement

CAUTION: EYE AND SKIN IRRITANT. Contains ethylene glycol. Do not swallow. Do not allow eye contact or prolonged skin contact. **First Aid:** If swallowed, do not induce vomiting; contact physician. If eye contact occurs, flush with water for 15 minutes. Wash skin contact areas with soap and water. If irritation from eye or skin contact areas persists, contact physician. For additional information, refer to Material Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

Ordering Information

Cat. No.	Size	Units per Package	Weight	Packages per Pallet
4122	29 oz. Cartridge	12	31	38

Important Notice: Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.

1.888.533.9043 Help Line
1.800.669.4583 Customer Service

TitebondGreenChoice.com
www.titebond.com

Franklin International

2020 Bruck Street Columbus, Ohio 43207

©2007 Franklin International. All rights reserved.