

**#BNS-2213 | UFO BALLISTIC NailScrews™ COMPATIBILITY CHART**

Asymmetrical threads offer minimal resistance during installation (but provide nearly the same pull-out resistance as the popular deep threaded screws used in self-feed screw guns). The 2-1/4" x 0.113" screws have a #2 Phillips recess, so they are easy to remove if necessary. Screws (nails) are yellow zinc plated, have blunt tips to help prevent splitting, and are collated in 20° plastic strips.

**Nail Gun Manufacturers and Compatible Models**

---

**Airy**ABL-8290

---

**Bostitch**RN90, N79RH, N88RH, N90RHN, N95RHN

---

**Campbell Hausfeld**NS2090 (2" to 3-1/2")

---

**Craftsman**18365 (2" to 3-1/2")

---

**DeWalt**D51845

---

**Duo-Fast**SNP-83, SNP83, SRN90, CN350, CN350B, CN350B-CH

---

**Fasco**R5C-RHN20-90SS

---

**GREX**SF9021

---

**Hitachi**NRH83A (up to 3-1/4"), NR90AA2, NR90AC, NR90AC2

---

**Holz-Her**3540, 3542, 3544, 3546, 3547

---

**Makita**AN8300, AN922 (.113 - .148)

---

**Max**SN890RH, SN89RH, SN90

---

**Paslode**5350/SRH20

---

**Porter Cable**FR3, FR350, FR350A

---

**Senco**SN60, SN65, 750XP, 600FRH, SN65C (up to .162" shank),  
FramePro 602 (up to 3-1/2"), 652 (up to 3-1/2"), 702XP,  
752XP (up to 3-1/2"), 700XL FRH, 650FRH (2-1/4" to  
3-1/2")

---

**SpotNails**NPR90

---