



Manufactured by:
Eclectic Products, Inc.
Pineville, LA 71361

Made in the USA

800.767.4667 - Technical Services

www.eclecticproducts.com

www.famowood.com

TECHNICAL DATA SHEET

***Famowood® Water-Based
Wood Filler***

PRODUCT DESCRIPTION

FAMOWOOD® WATER-BASED WOOD FILLER the #1 choice of woodworking professionals for over 50 years, has developed a water-soluble formula certified by Scientific Certification Systems as having no smog producing ingredients. Whether you're masking small or large defects, **FAMOWOOD®** can be used inside or outside and takes stains and paint evenly, making it ideal for any customer project. **FAMOWOOD®** spreads evenly into cracks and holes without shrinking, crumbling or cracking. In addition, **FAMOWOOD®** requires very little sanding to achieve a desired finished look.

PRODUCT CHARACTERISTICS and BENEFITS

High solid content	Saw, drill, sand, plane and nail, just like real wood
Fast dry time	Can be indoors and outdoors
Easy application	Spreads evenly into cracks and holes without crumbling or cracking
Superior strength	Hard finish with little or no shrinkage
Quality finish	Takes stains and paints evenly with minimal sanding

PHYSICAL PROPERTIES

Color(s)	Birch, Cherry/Dark Mahogany, Fir/Maple, Golden Oak, Natural, Oak, Red Oak, Walnut, White, White Pine (10 colors)
Density	15.0 - 16.0 lbs/gal
Solids	82% ± 2.0% (by weight)
Storage	Store between 45°F (7°C) and 85°F (29°C)
Freeze/thaw stability	Stable up to three to five freezes; allow product to warm to room temperature before using
Shelf life	1-1/2 years

DIRECTIONS FOR USE / APPLICATION NOTES

Please read all directions before using. Always test a small area before full use.

- Step 1** For best adhesion, cracks or defects should be clean and dry.
- Step 2** Press firmly into defect by hand, or with putty knife.
- Step 3** A thin film will dry within minutes. Lower temperatures require longer drying periods.
- Step 4** When dry, sand flush with surrounding surfaces.
- Step 5** Surfaces may be painted, varnished, lacquered, waxed, or shellacked.
- Step 6** Clean tools while still wet with water or soap with water. If product has dried on tools, use chlorinated solvent or steam.
- Step 7** Close container after each use.

For technical assistance, call 800.767.4667.

- FAMOWOOD® Water-Based Wood Filler can be drilled, nailed, planed, or sawed like ordinary wood.
- Use water to restore wood filler to its original consistency.

TECHNICAL DATA SHEET

HAZARDS

Before working with this product, read and become familiar with information concerning hazards, proper use and handling. To request an MSDS, please send an Email to msds@eclecticproducts.com or call 800.333.9826.

LIMITED WARRANTY

The product is warranted against any defect in materials or workmanship under normal use and service for a period of 180 days after the date of purchase. The product is also warranted under any implied warranties provided under applicable state law, including, without limitation, the implied warranty of merchantability and the implied warranty of fitness for a particular purpose, for a period of 180 days after the date of purchase. This warranty covers only the original buyer of the product. For warranty service, the buyer should contact the store where the product was purchased, or write Eclectic Products, Inc. P.O. Box 4450, Pineville, LA 71360 or call 800.767.4667. This warranty gives you specific legal rights, and you also have other rights, which vary from state to state.

WOOD FILLER COMPARISON TEST

Five comprehensive tests

Dry time
Shrinkage
Adhesion
Stainability
Sanding

Results

FAMOWOOD WATER-BASED WOOD FILLER came out on top for overall superiority.

Average of Total Test Scores

